



Product data sheet


2way, 1-pole intermediate switch, 10A











Reference number

IPK6.10-201-01.M

Flush mount 2way, 1-pole intermediate switch 10A/250V~, without frame

1 pole
1 mm. thickness metal supporting frame, for claw or screw mounting;
screwless terminals for wires up to 2.5 mm²

Intended use

- dept 27mm
- installation in flush box according to DIN 49073
- operation with suitable cover
- fits to all Modern serie frames

Centre plates colour, EAN code:

IPK6.10-201-01.M/WM - White matt, 4770025003893, 10pc. package code 4770025003909;
"10pc.profi box": 4770025003916;
IPK6.10-201-01.M/SM - Sandy matt, 4770025005231, 10pc. package code 4770025005248 ;
IPK6.10-201-01.M/CH - Champagne, 4770025004531, 10pc. package code 4770025004548;
IPK6.10-201-01.M/BM - Black matt, 4770025005859, 10pc. package code 4770025005866;

Technical specifications:

Input voltage, frequency	AC 250 V +- 10% , 50/60 Hz
	IP20
Standarts	EN 50581
	EN 60669-1
	Low-Voltage Directive 2014/35/EU
	RoHS Directive 2011/65/EU
Switching current	10A
Ambient temperature	-5 ... +35 °C
Storage/transport temperature	-20 ... +40 °C
Connection	spring terminals
Centre plates material	breakproof polycarbonate (PC), matt
Custom tariff number	8536500700
Dimmensions, mm (HxWxD)	70x70x27

CE

MADE IN LITHUANIA SINCE 1944